



RAJ CERAMICS

S COMPOUNDS & FLUXES

The basic purpose of slag conditioner besides holding impurities is a white foamy porous cover which has various advantages.



Sl. No.	Brand	Al ₂ O ₃ % min	Florides % range	Acid Insoluble % range	CaO % range	MgO % range	C % range	Aluminium % range
1	RC - Ladlex	Specification Proprietary	-	-	-	-	-	-
2	Rc - Tunlex	Specification Proprietary	-	-	-	-	-	-
3	RC - Slag Conditioner	45	1.5	2 - 8	3	4	1	27
4	Rc - Almix	Specification Proprietary	-	-	-	-	-	-
5	RC - Carbosil	Specification Proprietary	-	-	-	-	-	-
6	RC - Synthetic Slag	Specification Proprietary	-	-	-	-	-	-
7	RC TP 8	Specification Proprietary	-	-	-	-	-	-
8	RC GM 40	Specification Proprietary	-	-	-	-	-	-



- 1. The above values represent values obtained on standard squares in accordance with accepted test methods and are subject to manufacturing variations. This information is supplied as a technical service and may change without notice. Results are only indicative data and should not be used for specification/guarantee purposes. Size tolerance $\pm 1.5\%$ or $\pm 2\text{mm}$ whichever ever is greater.
- 2. We also make Bricks on tailor-made specification
- 3. Grading means 90% passing through the desired sieve

